

VESTA-211N-720P

VST-892-IL-SF1 ALK



PIRCAM 720P detector for indoor use



- PIRCAM Vesta indoor detector
- PIR coverage of 10 meters, 90°
- Sensitivity configurable from APP
- Optics 102°, IR illumination of 7 meters
- 720P resolution
- Anti-masking function
- Anti-pet 20 kg / 50 cm
- Compatible with BOGP control panels
- EN50131 Grade 2 certified.



Reference / Model

VESTA-211N-720P / VST-892-IL-SF1 ALK

Detection range of 10 meters, 90°.

Advanced dynamic speed adjustment algorithms to adapt image transfer rate to signal quality

2.3 ~ 2.5 meters installation height

Anti-pets up to 20 kg / 50 cm

Blind spot free detection

Remotely adjustable sensitivity

Four alarm image processing options: 1280x720@3ips, 640x480@3ips, 320x240@3ips and 320x240@6ips

Image delivery on demand

Anti-masking function

Infrared nighttime illumination capability, up to 7 meters range

F1 technology accelerates transmission speed and increases communication range

Periodic monitoring signals

Tampering protection

VESTA-211N-720P

VST-892-IL-SF1 ALK



PIRCAM 720P detector for indoor use

Reference / Model	VESTA-211N-720P / VST-892-IL-SF1 ALK
	Low battery detection
	Suitable for security and home automation
	Compatible with Climax F1 gateways / control panels and VESTA-030 repeater (RP-29-F1)
	RF frequency: 868MHz
	Communication range 400 ~ 900 meters in open field
	10k, 20k, 30k, 50k, 80k data rate
	Detection range: 10 meters, 90°, installed at a height of 2.3 ~ 2.5 meters
	VGA CMOS sensor
	Horizontal viewing angle: 102°.
	Resolution: 640 x 480, 320 x 240
	Infrared illumination up to 7 meters
	Compatible with BOGP control panels
	Power supply: 2 x 1.5V AA alkaline batteries
	Battery life up to 4 years
	Operating temperature -10°C ~ +45°C (-10°C ~ +45°C)
	Relative humidity up to 85% (non-condensing)
	Dimensions: 63 (W) x 123 (H) x 45 mm
	EN50131 Grade 2 certified