

PIRCAM Vesta Indoor BUS Detector (V-MAX BUS)



ANTIMASKING



GRADE 2

- PIRCAM Vesta indoor BUS (V-MAX BUS) detector
- PIR coverage of 12 metres, 90°
- Sensitivity configurable from APP
- 102° optics, IR illumination of 7 metres
- Anti-masking function
- Anti-pet 20 kg / 50 cm
- EN50131 Grade 2 certified

**Reference / Model****VESTA-355 / 892-BUS**

Detection range of 12 metres, 90°.

Advanced dynamic rate adjustment algorithms to adapt image transfer rate to signal quality

2.3 ~ 2.5 metres installation height

Anti-pet up to 20 kg / 50 cm

Blind spot free detection

Remotely adjustable sensitivity

Three alarm image processing options: 640x480@3ips, 320x240@3ips and 320x240@6ips

On-demand image delivery (Photo-repetition)

Anti-masking function

Night illumination capability by infrared light, up to 7 metres range

Constant monitoring signals via V-MAX BUS

Tamper protection

Suitable for security and automation

PIRCAM Vesta Indoor BUS Detector (V-MAX BUS)

Reference / Model	VESTA-355 / 892-BUS
	V-MAX BUS communication
	BUS communication range use hybrid panel calculator
	Data rate of 20k, 30k, 40k, 40k, 80k
	Detection range: 12 metres, 90°, installed at a height of 2.3 ~ 2.5 metres
	VGA CMOS sensor
	Horizontal Viewing Angle: 102° Horizontal Viewing Angle: 102° Horizontal Viewing Angle: 102
	Resolution: 640 x 480, 320 x 240
	Infrared illumination up to 7 metres
	BUS-powered
	Operating temperature: -10°C ~ +45°C (-10°C ~ +45°C)
	Relative humidity up to 85% (non-condensing)
	Dimensions: 63 (W) x 123 (H) x 45 mm
	EN50131 Grade 2 certified