


32-channel NVR IP Pro AI-L Series



- Vesta Advanced Video Pro AI-L Series 32-channel NVR IP Vesta Advanced Video Pro AI-L Series
- H.265/H.264
- 256/256 Mbps input/output
- Simultaneous HDMI (4K) and VGA (1080P) outputs
- AI from cameras: Perimeter protection, face detection, people counting and SMD
- AI from NVR: Perimeter protection, face detection and SMD
- 2 SATA HDD capacity
- 1 RJ45 Gigabit
- 2 USB 2.0., 1 USB 3.0
- 12V DC



Reference / Model	NVR6232-PRO / NVR6232-PRO
32 IP channels	
Video compression: H.265 and H.264	
Simultaneous video outputs HDMI (4K) and VGA (1080P)	
Output division: 1, 4, 9, 16, 25, 32	
1 input / 1 output RCA audio	
Bi-directional audio	
Audio compression: G.711a	
Recording resolution up to 8MP (3840x2160)	
Bandwidth: 256 Mbps in, 256 Mbps out	
Decoding capacity:	
4 channels at 8MP (30 fps)	
16 channels 1080P (30 fps)	
Supports adaptive decoding	
Manual, scheduled recording modes (general, videosensor, alarm, intelligence)	
Alarm link: Recording, Image capture, Buzzer, Logging, Preset, Email	

32-channel NVR IP Pro AI-L Series

Reference / Model	NVR6232-PRO / NVR6232-PRO
	Supports image capture in JPEG format
	Artificial Intelligence from intelligent cameras:
	Perimeter protection (intrusion, line crossing).
	Face detection
	People counting
	Intelligent motion detection
	Artificial Intelligence in the recorder:
	Perimeter protection (intrusion, line crossing): Up to 2 channels
	Face detection: Up to 2 channels
	Intelligent motion detection: Up to 2 channels
	AI search by target classification (people, motorized vehicles and non-motorized vehicles)
	Synchronized playback of up to 16 channels
	Internal capacity for 2 SATA HDD up to 14TB (sold separately)
	Gigabit Ethernet RJ45 network port (10/100/1000Mbps)
	Network protocols: HTTP, TCP/IP, IPv4, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, P2P, Auto register
	Onvif and SDK support
	Compatible with IE8 or later web browser
	Compatible with Android and iOS devices
	Communication ports: 2 USB 2.0 ports, 1 USB 3.0 port
	Power supply: 12V DC, 3A
	Power consumption: 20 W (excluding hard disk)
	Operating temperature from -10°C ~ +55°C
	Relative humidity 10%~90% (non-condensing)
	Metal housing
	Dimensions: 360 (W) x 48 (H) x 311,5 mm (1U)
	Weight: 3 kg
	Desktop installation

NVR6232-PRO

NVR6232-PRO



32-channel NVR IP Pro AI-L Series

Reference / Model	NVR6232-PRO / NVR6232-PRO
-------------------	---------------------------

CE/FCC certified
